



- sv** Monteringsanvisning
*) Kan fås via Service
- no** Monteringsanvisning
*) Les hos kundeservice
- fi** Asennusohje
*) Saatavissa huoltopalvelusta
- da** Monteringsvejledning
*) Kan købes hos serviceafdelingen
- tr** Montaj kılavuzu
*) Yetkili servis üzerinden alınabilir
- ru** Инструкция по монтажу
*) Можно получить в сервисном центре
- cs** Montážní návod
*) K dispozici přes servisní službu
- pl** Instrukcja montażu
*) Do uzyskania w punkcie serwisowym
- es** Instrucciones de montaje
*) Se puede adquirir a través del Servicio de Asistencia Técnica Oficial de la marca
- hu** Szerelési utasítás
*) A vevőszolgálaton keresztül kapható.
- lt** Uputa za montažu
*) može dobiti kod službe održavanja
- mk** Упутство за монтажа
*) се добија преко службена за купувачи
- sl** Navodilo za montažo
*) Lahko nabavite v servisni službi
- sr** Uputstvo za montažu
*) Može se nabaviti preko servisne službe
- et** Monteerimisjuhend
*) Külsige klientideeninduselt
- lt** Montavimo instrukcija
*) Ją galima gauti klientų aptarnavimo servise
- lv** Montāžas pamācība
*) Var saņemt servisa dienestā
- sk** Návod na montáž
*) Dostanete v službe zákazníkom
- sq** Udhëzues për montim
*) Sigurohet nëpërmjet servisit
- bs** Uputa za montažu
*) Može se dobiti preko servisne službe
- fa** راهنمای مونتاژ
*) از مرکز خدمات پس از فروش تهیه فرمائید
- ar** تعليمات التركيب
*) يمكن طلبها من مركز خدمة العملاء
- ko** 설치 설명서
*) 고객센터 센터에서 구입 가능
- zh** 安装说明书
*) 可向售后服务站索取。
- uk** Інструкція з монтажу
*) Можна отримати через сервісну службу
- ro** Instrucțiune de montaj
*) obținabilă la serviciul pentru clienți
- id** Instruksi Pemasangan
*) bisa didapatkan melalui Customer Service
- kk** Сәке қосу туралы нұсқаулар!
*) Сервис қызмет көрсету орталығында алуға болады

1

1.75 m
ø 4x15
ø 4x30
ø 4x15
ø 4x42
ø 4x28

2a

*) Mat-Nr. 10011641

2b

3

nicht einklemmen
do not pinch
ne pas coincier
No doblar

verspannen
brace
calar verticalamente
Enrasar

0-60 mm
SW 13
SW 10

5

max. 725
444
max. 1.2 mm
2.5 - 7.5 kg

6

7

einstellen
adjust
régler
ajustar

min. 70 mm
max. 120 mm

>120 mm

min. 70 mm
max. 120 mm

9

10

11

Scheibe entfernen
remove disc
enlever le disque
Eliminar Disco

min. ø 18 mm

max. 10 Nm

10 l/min

Dichtheit nach einem Spülgang prüfen.
Check for leaks after one wash cycle.
Vérifiez l'étanchéité après un lavage.
Verificar la estanqueidad tras un ciclo de lavado.

ø 38 mm
max. 1.1 m
min. 280 mm

26.4 mm 20.9 mm
(G 3/4") (G 1/2")

min. 10 mm

0,05 - 1 MPa
(0.5 - 10 bar)
max. 60°C

FI =

max. 4 m
2 m
ø 22 mm
2.2 m
Mat-Nr. 00350564

5 m
EU *) Mat-Nr. 12022522

GV 44x Voll-I - K-SW GS 9001 881 895 (0310)



